

1600 Series 1500 rev/min Diesel Engine – Electropak

1606D-E93TAG4 275 kVA Prime Power / 300 kVA Standby Power

1606D-E93TAG5 300 kVA Prime Power / 330 kVA Standby Power

Building upon Perkins proven reputation within the power generation industry, our 1600 Series Electropak engines now fit even closer to our customers needs.

The 1606D engine is a full authority electronic, 6 cylinder engine. It is economical and quiet and provides the close speed control and reliable, high performance that are demanded by our customers for their power generation business.

Focusing on our common platform theme, changes to engine envelope dimensions and connection points have been kept to a minimum, meaning that there is an easy changeover from 1300 Series to 1600 Series.



Dependable power

- The Perkins 1606D-E93TAG4 and TAG5 deliver up to 300 kVA and 330 kVA 50 Hz standby power respectively, providing greater productivity through an improved power to weight ratio.

This world-class power density has been achieved in 9.3 litre turbocharged engines with a hydraulic actuated unit injector fuel system; making these engines robust for all markets because of their ability to cope with the variation of fuel quality around the world.

- The 1606D has been designed to run in the harshest conditions; from the lowest to highest ambient temperatures: -40°C to 55°C.

Low operating costs

- Service intervals are set at 300 hours as standard.
- We use the appropriate technology when and where needed which ensures low cost of ownership, simple maintenance and reduced downtime.
- The 1600 Series engine design offers common components to reduce parts inventory, for example filters, cylinder heads, blocks and pistons.
- Perkins provides comprehensive warranty cover for two years (up to 3,000 hours), with three years on major engine components.

Flexibility

- The 1606D range has been designed to hit all the main power nodes.
- Tropical radiator is offered as standard.
- High power density helps reduce installation costs and is easily packaged.

World class product support

- Our experienced global network of distributors and dealers, fully trained engine experts deliver total service support around the clock, 365 days a year. They have a comprehensive suite of web based tools at their finger tips, covering technical information, parts identification and ordering systems, all dedicated to maximising the productivity of your engine.
- Perkins actively pursues product support excellence by insisting our distribution network invest in their territory to provide you with a consistent quality of support across the globe.
- Throughout the entire life of a Perkins engine, we provide access to genuine OE specification parts giving 100% reassurance that you receive the very best in terms of quality for lowest possible cost... wherever your Perkins powered machine is operating in the world.

Engine Model (1500 rev/min)	Type of Operation	Typical Generator Output (Net)		Net Engine Power	
		kVA	kWe	kWm	hp
1606D-E93TAG4	Prime Power	275	220	239	320
	Standby (maximum)	300	240	261	350
1606D-E93TAG5	Prime Power	300	240	261	350
	Standby (maximum)	330	264	287	385

Photographs are for illustrative purposes only and may not reflect final specification.

All information in this document is substantially correct at time of printing and may be altered subsequently.
Publication No. PN3046/10/13 Produced in England ©2013 Perkins Engines Company Limited

 **Perkins®**

THE HEART OF EVERY GREAT MACHINE

1600 Series

1500 rev/min Diesel Engine – Electropak

1606D-E93TAG4 275 kVA Prime Power / 300 kVA Standby Power

1606D-E93TAG5 300 kVA Prime Power / 330 kVA Standby Power

Standard Electropak specification

Air inlet

- Mounted air filter and turbocharger

Fuel system

- High pressure G2 fuel system with full authority electronic control
- Electronic governing to ISO 3046-4 with stand-alone isochronous and load-sharing capabilities
- Replaceable element fuel filter with pre-filter and hand primer pump

Lubrication system

- Wet front well steel sump with filler and dipstick
- Full flow spin-on filters
- Stacked plate-type oil cooler thermostatically controlled

Cooling system

- Thermostatically controlled with belt driven circulating pump and 36 inch belt-drive fan
- Radiator supplied loose with all guards and pipes
- Air-to-air charge cooler incorporated in radiator

Electrical equipment

- 24V starter motor and 24V 45 amp alternator with DC output
- Electronic Control Module (ECM) mounted on engine with wiring looms and sensors
- 3 level engine protection system

Flywheel and housing


- High inertia flywheel to SAE 1 J620 Size 355.6 mm (14 in)
- Cast iron SAE 1 flywheel housing

Mountings

- Front engine mounting bracket

Optional equipment

- Sensor positions for:
 - oil pressure
 - oil temperature
 - coolant temperature
- Turbocharger exhaust outlet
- Parts Book
- Service Manual



Engine data

Number of cylinders	Vertical in-line 6 cylinder
Bore and stroke.....	117 x 146 mm (4.6 x 5.7 in)
Displacement	9.3 litres (567 cubic in)
Aspiration	Turbocharged aftercooled
Cycle.....	4 stroke
Combustion system.....	Direct injection
Compression ration	17.2:1
Engine rotation	Anti-clockwise viewed on flywheel
Cooling system.....	Liquid
Total lubrication capacity.....	36 litres (9.5 US gal)
Dimensions – Length – including air cleaner ...	1964 mm (77.3 in)
Width	1074 mm (42.3 in)
Height	1354 mm (53.3 in)
Dry weight	959 kg (2114 lbs)

Final weight and dimensions will depend on completed specification

Photographs are for illustrative purposes only and may not reflect final specification.

All information in this document is substantially correct at time of printing and may be altered subsequently.
Publication No. PN3046/10/13 Produced in England
©2013 Perkins Engines Company Limited

Perkins Engines Company Limited

Peterborough PE1 5FQ

United Kingdom

Telephone +44 (0)1733 583000

Fax +44 (0)1733 582240

www.perkins.com

 **Perkins**[®]

THE HEART OF EVERY GREAT MACHINE